

## SPECIFICATION OF HILO BRAND RADIAL OTR,

2007.4.9

SIZE	INTENSITY	TYPE	PATTERN	TREAD DEPTH (mm)	STANDARD RIM	INFLATED OVERALL DIAMETER(mm)		STANDARD AIR PRESSURE (Bar)	LOAD INDEX	MAX LOAD (kgs)	MAX SPEED (KM/H)	WEIGHT KG	ADOPTED STANDARD
						Overall Diameter +/-1.5%	Section Width +/-3.5%						
17.5R25	2 STAR	E3	XB01N	28	14.00/1.5	1348	445	5.75/4.5	182/167	8500/5450	10/50	150	ETRTO,TRA,GB/T2980
20.5R25	2 STAR	E3	XB01N	31	17.00/2.0	1492	520	6.50/5.25	193/177	11500/7300	10/50	255	
23.5R25	2 STAR	E3	XB01N	34	19.50/2.5	1617	597	6.50/5.25	201/185	14500/9250	10/50	330	
26.5R25	2 STAR	E3	XB02N	37	22.00/3.0	1750	673	5.75/4.5	209/193	18500/11500	10/50	450	
29.5R25	2 STAR	E3	XB02N	43.5	25.00/3.5	1873	750	5.75/4.5	216/200	22400/14000	10/50	585	
18.00R25	2 STAR	E4	XB06S	47	13.00/2.5	1673	498	8.00/6.5	204/185	16000/9250	10/50	395	
18.00R33	2 STAR	E4	XB06S	54	13.00/2.5	1877	498	8.00/6.5	209/191	18500/10900	10/50	465	
16.00R25	3 STAR	E2	XB05N/XBGZN	28	11.25/2.0	1493	432	6.9	179	7400	70	225	



**XB01N**



**XB02N**



**XBGZN**



**XB05N**



**XB06S**

# **SPECIFICATION OF HILO BRAND RADIAL OTR,**

2007.5.8

SIZE	INTENSITY	TYPE	PATTERN	TREAD DEPTH (mm)	STANDARD RIM	INFLATED OVERALL DIAMETER(mm)		STANDARD AIR PRESSURE (Bar)	LOAD INDEX	MAX LOAD (kgs)	MAX SPEED (KM/H)	WEIGHT KG	ADOPTED STANDARD
						Overall Diameter	Section Width						
						+/-1.5%	+/-3.5%						
29.5R25	2 STAR	E3	XB02N	43.5	25.00/3.5	1873	750	5.75/4.5	216/200	22400/14000	10/50	585	ETRTO,TRA,GB/T2980
29.5R25	2 STAR	E4	XBDTS	57	25.00/3.5	1885	750	5.75/4.5	216/200	22400/14000	10/50	648	

**XB02N(E3)**



**XB02N(E3) \* THE PATTERN BEING ADJUSTED TO THIS.**



**XBDTS(E4) \* DEEP TREAD DEPTH**

